



Etherea with nanoe™ X Pure White Matt R32



Noul Etherea cu tehnologie nanoe™ X

[AFLAȚI MAI MULTE](#)



Etherea cu nanoe™ X Alb pur mat R32

		5.0 kW
Kit		KIT-Z50-XKE
Cooling capacity (Nominal)	kW	5,00
Cooling capacity (Min)	kW	0,98
Cooling capacity (Max)	kW	6,00
EER (Nominal) (1)	W/W	3,68
EER (Min) (1)	W/W	3,92
EER (Max) (1)	W/W	3,16
SEER (2)		8,50 A+++
Pdesign (cooling)	kW	5
Input power cooling (Nominal)	kW	1,36
Input power cooling (Min)	kW	0,25
Input power cooling (Max)	kW	1,90
Annual energy consumption cooling (3)	kWh/a	206,00
Heating capacity (Nominal)	kW	5,80
Heating capacity (Min)	kW	0,98
Heating capacity (Max)	kW	8,00
Heating capacity at -7°C	kW	4,80
COP (Nominal) (1)	W/W	4,14
COP (Min) (1)	W/W	4,26
COP (Max) (1)	W/W	3,35
SCOP (2)		4,80 A++
Pdesign at -10°C	kW	4,2
Input power heating (Nominal)	kW	1,40
Input power heating (Min)	kW	0,23
Input power heating (Max)	kW	2,39

Etherea cu nanoe™ X Alb pur mat R32

5.0 kW

Annual energy consumption heating (3)	kWh/a	1225
Indoor unit		CS-Z50XKEW
Indoor power source	V	230
Indoor recommended fuse	A	16
Indoor connection indoor / outdoor	mm ²	4 x 2,5
Indoor air flow (Cool)	m ³ /min	17,4
Indoor air flow (Heat)	m ³ /min	19,1
Moisture removal volume	L/h	2,8
Indoor sound pressure (Cool -Hi) (4)	dB(A)	44
Indoor sound pressure (Cool -Hi) (4)	dB(A)	44
Indoor sound pressure (Cool -Lo) (4)	dB(A)	37
Indoor sound pressure (Cool -Q-Lo) (4)	dB(A)	30
Indoor sound pressure (Heat -Hi) (4)	dB(A)	44
Indoor sound pressure (Heat -Lo) (4)	dB(A)	37
Indoor sound pressure (Heat -Q-Lo) (4)	dB(A)	30
Indoor dimension (Height)	mm	295
Indoor dimension (Width)	mm	1040
Indoor dimension (Depth)	mm	244
Indoor net weight	kg	12
nanoe X Generator		Mark 2

Etherea cu nanoe™ X Alb pur mat R32

		5.0 kW
Outdoor unit		CU-Z50XKE
Outdoor air flow (Cool)	m ³ /min	39,8
Outdoor air flow (Heat)	m ³ /min	36,9
Outdoor sound pressure (Cool -Hi) (4)	dB(A)	47
Outdoor sound pressure (Cool -Hi) (4)	dB(A)	47
Outdoor sound pressure (Heat -Hi) (4)	dB(A)	47
Outdoor dimension (Height) (5)	mm	695
Outdoor dimension (Width) (5)	mm	875
Outdoor dimension (Depth) (5)	mm	320
Outdoor net weight	kg	40
Pipe diameter (Liquid)	Inch (mm)	1/4 (6,35)
Pipe diameter (Gas)	Inch (mm)	1/2 (12,70)
Pipe length range	m	3 ~ 30
Elevation difference (in/out) (6)	m	15
Pipe length for additional gas	m	7,5
Additional gas amount	g/m	15
Refrigerant (R32) / CO2 Eq.	kg / T	1,13 / 0,76
Operating range (Cool - Min)	°C	-10
Operating range (Cool - Min)	°C	-10
Operating range (Cool - Max)	°C	43

Etherea cu nanoe™ X Alb pur mat R32

5.0 kW

Operating range
(Heat - Min)

°C

-15

Operating range
(Heat - Max)

°C

24

Produce complementare



CZ-CAPRA1 RAC interface adapter for integration into P Link



Wired Remote Control CZ-RD514C



PAW-SMSCONTROL. Control by SMS (need additional SIM card).



CZ-RD517C. Wired remote controller for wall-mounted and floor console